

Abmessungen / Technische Daten

Artikel-Nr. Ketten Fuchs	Abmessungen in mm			Spannschrauben		Übertragungswerte				Gewicht kg	
	Größe d×D	H	h ₁	Anzahl Stück	Größe M	M _d Nm	Dreh- moment M _t Nm	Axial- Kraft F _{ax} kN	Flächen- Druck P _w N/mm ²		Nabe P _N N/mm ²
145-150200	150×200	130,0	116,0	15	M14×90	230	68668	916	222	166	11,000
145-160210	160×210	130,0	116,0	16	M14×90	230	78129	977	222	169	12,000
145-170225	170×225	162,0	146,0	14	M16×110	355	98098	1154	195	147	17,000
145-180235	180×235	162,0	146,0	16	M16×110	355	118707	1319	210	161	18,400
145-190250	190×250	162,0	146,0	16	M16×110	355	125302	1319	199	151	21,400
145-200260	200×260	162,0	146,0	16	M16×110	355	131896	1319	189	145	21,800
145-220285	220×285	162,0	146,0	20	M16×110	355	181357	1649	215	166	26,590
145-240305	240×305	162,0	146,0	22	M16×110	355	217629	1814	217	170	28,700
145-260325	260×325	162,0	146,0	21	M16×110	355	225048	1731	191	153	31,230
145-280355	280×355	197,0	177,0	18	M20×130	690	323016	2307	186	147	46,770
145-300375	300×375	197,0	177,0	20	M20×130	690	384543	2564	193	154	49,720
145-320405	320×405	197,0	177,0	21	M20×130	690	430688	2692	190	150	60,520
145-340425	340×425	197,0	177,0	22	M20×130	690	479397	2820	187	150	63,860
145-360455	360×455	225,0	203,0	21	M22×130	930	593686	3298	180	142	86,780
145-380475	380×475	225,0	203,0	22	M22×130	930	656509	3455	178	143	91,040
145-400495	400×495	225,0	203,0	24	M22×130	930	753886	3769	185	149	95,300