

Hakon®-Spannsätze Baureihe 160 Wellenkupplungen

Abmessungen / Technische Daten

Artikel-Nr. Ketten Fuchs	Abmessungen in mm				Spannschrauben		Übertragungswerte			Gewicht kg
	Größe d×D	H	h ₁	h ₃	Größe M	M _d Nm	Dreh- moment M _t Nm	Axial- Kraft F _{ax} kN	Flächenpressung Welle P _w N/mm ²	
160-4285	42 × 85	93,0	85,0	22,0	M8 × 75	41	1100	52	190	1,89
160-4585	45 × 85	93,0	85,0	22,0	M8 × 75	41	1200	53	177	1,96
160-4890	48 × 90	93,0	85,0	22,0	M8 × 75	41	1300	54	168	2,20
160-5090	50 × 90	93,0	85,0	22,0	M8 × 75	41	1350	54	159	1,88
160-5595	55 × 95	93,0	85,0	22,0	M8 × 75	41	1900	69	193	2,29
160-60100	60 × 100	93,0	85,0	22,0	M8 × 75	41	2100	70	177	2,44
160-65110	65 × 110	93,0	85,0	22,0	M8 × 75	41	2350	72	163	2,65
160-68115	68 × 115	110,0	100,0	35,0	M10 × 80	83	2850	84	119	4,00
160-70115	70 × 115	110,0	100,0	35,0	M10 × 80	83	3150	90	116	4,10
160-75120	75 × 120	110,0	100,0	35,0	M10 × 80	83	3400	91	108	4,28
160-80125	80 × 125	110,0	100,0	35,0	M10 × 80	83	4900	123	135	4,49
160-85130	85 × 130	110,0	100,0	35,0	M10 × 80	83	5250	124	127	4,86
160-90135	90 × 135	110,0	100,0	35,0	M10 × 80	83	5530	123	120	5,05
160-100155	100 × 155	132,0	120,0	40,0	M12 × 110	143	8500	170	136	8,00
160-110170	110 × 170	132,0	120,0	40,0	M12 × 110	84	9600	175	109	9,10