

Z	d _e	d _p	einfach			zweifach			dreifach		
			d _m	D ₁	A	d _m	D ₁	A	d _m	D ₁	A
8	115,0	99,55	58	20	45	58	25	95	28	25	140
9	126,4	111,40	70	20	45	70	25	95	70	25	140
10	138,0	123,29	80	20	45	80	25	95	80	25	140
11	150,0	135,21	90	25	50	90	25	100	90	25	150
12	162,0	147,22	102	25	50	102	25	100	102	25	150
13	174,2	159,18	114	25	50	114	25	100	114	25	150
14	186,2	171,22	128	25	50	128	25	100	128	25	150
15	198,2	183,26	140	25	50	140	25	100	140	25	150
16	210,3	195,30	140*	25	55	150*	25	100	150*	25	150
17	222,3	207,34	140*	25	55	150*	25	100	150*	25	150
18	234,3	219,42	140*	25	55	160*	25	100	160*	25	150
19	246,5	231,49	140*	25	55	160*	25	100	160*	25	150
20	258,6	243,57	140*	25	55	160*	25	100	160*	25	150
21	270,6	255,65	150*	25	60	160*	25	100	160*	30	150
22	282,7	267,73	150*	25	60	160*	25	100	160*	30	150
23	294,8	279,80	150*	25	60	160*	25	100	160*	30	150
24	306,8	291,88	150*	25	60	160*	25	100	160*	30	150
25	319,0	304,00	150*	25	60	160*	25	100	160*	30	150
26	331,0	316,08	160*	30	60	160*	30	100	160*	30	150
27	343,2	328,19	160*	30	60	160*	30	100	160*	30	150
28	355,2	340,27	160*	30	60	160*	30	100	160*	30	150
29	367,3	352,38	160*	30	60	160*	30	100	160*	30	150
30	379,5	364,50	160*	30	60	160*	30	100	160*	30	150
31	391,6	376,62	160*	30	60	170*	30	100	170*	30	150
32	403,7	388,69	160*	30	60	170*	30	100	170*	30	150
33	415,8	400,81	160*	30	60	170*	30	100	170*	30	150
34	427,8	412,93	160*	30	60	170*	30	100	170*	30	150
35	440,0	425,04	160*	30	60	170*	30	100	170*	30	150
36	452,0	437,16	160*	30	60	170*	30	100	170*	30	150
37	464,2	449,27	160*	30	60	170*	30	100	170*	30	150
38	476,2	461,39	160*	30	60	170*	30	100	170*	30	150
39	488,5	473,50	160*	30	60	170*	30	100	170*	30	150
40	500,6	485,62	160*	30	60	170*	30	100	170*	30	150

Kettenrad 1 1/2 x 1 "

für Rollenkette
nach DIN 8180/8187
ISO/R 606

* Kettenräder mit angeschweißter Nabe

Kettenrad	ISO mm	ASA-120 mm
Zahnkopfrundung r ₃	38	40,5
Breite der Rundung C	4	4,8
Zahnkranzbreite B ₁	24,1	23,5
Zahnkranzbreite b ₁	23,6	22,9
Zahnkranzbreite B ₂	72	68,3
Zahnkranzbreite B ₃	120,3	113,7

Kette	mm	mm
Teilung	38,1	38,1
innere Breite	25,4	25,4
Rollen-Ø	25,4	22,22

Z	d _e	d _p	S D ₁	D D ₂	T D ₃	Z	d _e	d _p	S D ₁	D D ₂	T D ₃
9	125,0	111,40	20	25	25	42	525,5	509,85	30	40	
10	137,0	123,29	20	25	25	43	538,0	521,97			
11	149,0	135,21	25	25	30	44	550,0	534,08	30		
12	161,0	147,22	25	25	30	45	562,0	546,20	30	40	40
13	173,0	159,18	25	25	30	46	574,0	558,32	30		
14	185,0	171,22	25	25	30	47	586,5	570,43			
15	197,0	183,26	25	25	30	48	598,5	582,55	30	40	40
16	209,0	195,30	25	30	30	49	610,5	594,66			
17	221,0	207,34	25	30	30	50	622,5	606,78	30	40	40
18	233,0	219,42	25	30	30	51	635,0	618,89			
19	245,5	231,49	25	30	30	52	647,0	631,01	30		
20	257,5	243,57	25	30	30	53	659,0	643,13			
21	270,5	255,65	30	30	40	54	671,0	655,25	30		
22	282,5	267,73	30	30	40	55	683,5	667,40	30		
23	294,5	279,80	30	30	40	56	695,5	679,50	30		
24	307,0	291,88	30	30	40	57	707,5	691,63	30	40	40
25	319,0	304,00	30	30	40	58	719,5	703,74			
26	331,0	316,08	30	30	40	59	731,5	715,86			
27	343,0	328,19	30	30	40	60	745,0	727,97	30	40	40
28	355,0	340,27	30	30	40	62	769,0	725,24	40		
29	367,5	352,38	30	30		64	793,5	776,48			
30	379,5	364,50	30	40		65	805,5	788,59	40	40	
31	391,5	376,62	30	40		66	817,5	800,71			
32	403,5	388,69	30	40	40	68	842,0	824,98			
33	415,5	400,81	30	40		70	866,0	849,21	40		
34	428,0	412,93	30	40		72	890,5	873,48			
35	440,0	425,04	30	40	40	75	926,5	909,83			
36	452,0	437,16	30	40		76	939,0	921,98	40	40	40
37	464,0	449,27	30	40		80	987,5	970,44	40		
38	476,5	461,39	30	40	40	85	1048,0	1031,10	40		
39	488,5	473,50	30	40		95	1169,0	1152,33	40		
40	501,5	485,62	30	40	40						

Kettenradscheibe 1 1/2 x 1 "

für Rollenkette
nach DIN 8180/8187
ISO/R 606

Kettenrad	ISO mm	ASA-120 mm
Zahnkopfrundung r ₃	38	40,5
Breite der Rundung C	4	4,8
Zahnkranzbreite B ₁	24,1	23,5
Zahnkranzbreite b ₁	23,6	22,9
Zahnkranzbreite B ₂	72	68,3
Zahnkranzbreite B ₃	120,3	113,7

Kette	mm	mm
Teilung	38,1	38,1
innere Breite	25,4	25,4
Rollen-Ø	25,4	22,22